

**Clean Earth Sampling Protocol
Connecticut**

	PARAMETERS	TOTAL PETROLEUM HYDROCARBONS (TPH)	TCL VOLATILE ORGANICS	TCL SEMI-VOLATILE ORGANICS *	TCLP Benzene	PCBs	TOTAL METALS - 8 RCRA	TCLP Lead	IGNITABILITY	TOTAL CYANIDE	TCL PESTICIDES	Total HERBICIDES	PAINT FILTER TEST	RADIOACTIVITY			
METHODS (1)		8015B or CT ETPH	8260B	8270D	1311/ 8260B	8082A	6010/ 7471	1311/ 6010A	1010A	9010	1311/ 8081B	1311/ 8151A	9095				
	FREQUENCY																
VIRGIN MATERIAL (Unused Products - Fuel Oils (#2, #4, and #6), Diesel, Hydraulic Oil)	3-point composite sample every 250 cy	a	a	a			a					b	b	a	d		
VIRGIN MATERIAL (Unused Products - Gasoline, Jet Fuel, Kerosene, and Aromatic and Aliphatic Hydrocarbons)	3-point composite sample every 250 cy	a	a	a	c			c,e	a			b	b	a	d		
Limit (mg/kg)		Oils: <100,000 Gas: <30,000			<0.5 mg/L	<50		<5.0 mg/L	Negative	<200				No Free Liquids			
WASTE MATERIAL (Used Products - Lubricating Oil, Cutting Oil, Water Soluble Oil, Hydraulic Oil, Quench Oil, and Aliphatic and Aromatic Hydrocarbons)	3-point composite sample every 250 cy	X	X	X			X	X				X	f	b	b	X	d
Limit (mg/kg)		Oils: <100,000 Gas: <30,000			<0.5 mg/L	<50		<5.0 mg/L	Negative	<200				No Free Liquids			
MGP (Coal Tar)	3-point composite sample every 250 cy	X	X	X			X	X				X	X	b	b	X	d
Limit (mg/kg)		Oils: <100,000 Gas: <30,000			<0.5 mg/L	<50		<5.0 mg/L	Negative	<200				No Free Liquids			

Notes:

- The methods provided are standard EPA methods. The method revisions are subject to change and the most current method should always be utilized by the laboratory.
- This is to be used as a guideline for sampling. Sampling frequencies and parameter requirements may be modified at the discretion of the CE Approval staff based on items such as site history, levels of contamination and/or
- When Virgin Material is spilled or released with used products or is spilled into urban fill, Waste Material protocol is required.
- TCLP analysis is required for VOCs, SVOCs, Metals, Pesticides and/or Herbicides if total concentrations of individual constituents exceeds 20 times the RCRA Toxicity Characteristic concentrations.

* - Total Chlorinated Solvents must be <1,000 mg/kg.

X - Analysis is required.

a - Written certification from the generator may be used in lieu of analytical results.

b - Written certification from the generator may be used in lieu of analytical results, unless Site History information indicates pesticides and/or herbicides were used, applied, or spilled.

c - Soil from aboveground storage tanks containing gasoline requires TCLP Benzene and TCLP Lead analysis. Soil from underground storage tanks containing gasoline requires TCLP Lead analysis only.

d - Written certification from the generator that identifies that the contaminated media is not radioactive in accordance with NRC and/or DOE regulations may be used instead of testing.

e - Written certification from the generator may be used in lieu of actual TCLP testing unless Site History information indicates the gasoline spill was prior to 1986.

f - Analysis for cyanide shall be performed on all media where cyanide was used; otherwise, written certification from the generator may be used in lieu of analytical results.